



# The Model T200

## Chemiluminescence NO/NO<sub>2</sub>/NO<sub>x</sub> Analyzer



The Model T200 NO / NO<sub>2</sub> / NO<sub>x</sub> analyzer uses the proven chemiluminescence detection principle and advanced electronics to allow accurate, dependable, continuous measurements for ambient air quality, stack gas monitoring and other applications.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- All other T Series instrument platform features
- Lifetime technical support by phone and email
- Standard two-year warranty

# T200 Specifications

■ Ranges	Min: 0 - 50 ppb full scale Max: 0 - 20,000 ppb full scale (selectable, dual-range supported)
■ Measurement Units	ppb, ppm, $\mu\text{g}/\text{m}^3$ , $\text{mg}/\text{m}^3$ (selectable)
■ Zero Noise	< 0.2 ppb (RMS)
■ Span Noise	< 0.5% of reading (RMS) above 50 ppb
■ Lower Detectable Limit	0.4 ppb
■ Zero Drift	< 0.5 ppb/24 hours
■ Span Drift	< 0.5% of full scale/24 hours
■ Lag Time	20 seconds
■ Rise/Fall Time	< 60 seconds to 95%
■ Linearity	1% of full scale
■ Precision	0.5% of reading above 50 ppb
■ Sample Flow Rate	500 cc/min $\pm$ 10%
■ Power Requirements	100V-120V, 220V-240V, 50/60 Hz
■ Analog Output Ranges	10V, 5V, 1V, 0.1V (selectable)
■ Recorder Offset	$\pm$ 10%
■ Included I/O	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 8 x opto-isolated digital outputs 6 x opto-isolated digital inputs 4 x analog outputs
■ Optional I/O	1 x USB com port 1 x RS485 8 x analog inputs (0-10V, 12-bit) 4 x digital alarm outputs Multidrop RS232 3 x 4-20mA current outputs
■ Operating Temperature Range	5 - 40°C (with US EPA approval)
■ Dimensions (HxWxD)	7" x 17" x 23.5" (178 x 432 x 597 mm)
■ Weight	Analyzer: 40 lbs (18 kg) External pump: 15 lbs (7 kg)
■ Certifications	US EPA: RFNA-1194-099 EU: EN14211 TÜV Rheinland QAL1 Certified: EN15267 MCerts: Sira MC050068/11 CNEMC: 质(认)字 No. 2015-028 Report

Specifications subject to change without notice.  
All specifications are based on constant conditions.

**For more information, contact us :**  
**Pacwill Environmental**  
 905.563.9097  
 Toll-Free (Canada): 1-866-840-0014

**sales@pacwill.ca**  
**www.pacwill.ca**