

## The Model T703 Photometric O<sub>3</sub> Calibrator



The Model T703 Photometric  $O_3$  calibrator combines an ozone generating device and photometer to provide a specified ozone concentration by volume for precision gas analyzers.

— With NumaView™ premium T Series software —

- Large, vivid, and durable color touchscreen display
- Lifetime technical support by phone and email
- All other T Series instrument platform features
- Standard two-year warranty





## T703 Specifications

System	<ul> <li>Linearity</li> </ul>	$\pm$ 1% of full scale
	<ul> <li>Precision</li> </ul>	1.0 ppb
	<ul> <li>Response Time</li> </ul>	< 180 seconds to 95%
	<ul> <li>Stability (7 days)</li> </ul>	< 1% with photometer feedback < 3% without photometer feedback (CNST or REF
Ozone Generator Module	<ul> <li>Flow Rate (with internal zero air source)</li> </ul>	1 to 5 LPM adjustable
	<ul> <li>Flow Rate (with external zero air source)</li> </ul>	1 to 15 LPM adjustable
	<ul> <li>Maximum Output</li> </ul>	5 LPM
	<ul> <li>Minimum Output</li> </ul>	100 ppb LPM
	<ul> <li>Maximum Concentration</li> </ul>	5 ppm at 1 LPM
	<ul> <li>Minimum Concentration</li> </ul>	50 ppb at 2 LPM
	<ul> <li>Response Time</li> </ul>	< 180 seconds to 98%
UV Photometer	Range	0 - 100 ppb to 0 - 10 ppm (selectable)
	<ul> <li>Precision</li> </ul>	1.0 ppb
	<ul> <li>Linearity</li> </ul>	± 1% of full scale
	<ul> <li>Rise/Fall Time</li> </ul>	< 20 seconds to 95% (photometer response)
	<ul> <li>Response Time</li> </ul>	< 180 seconds to 95% (system response)
	<ul> <li>Zero Drift</li> </ul>	< 1.0 ppb/7 days
	Span Drift	< 1%/24 hours
	Lag Time	< 10 seconds
	<ul> <li>Flow Rate</li> </ul>	800 cc/min ±10%
Electrical Specifications Communications Specifications	<ul> <li>Power Requirements</li> </ul>	100V-120V, 220V-240V, 50/60 Hz
	<ul> <li>Analog Output Ranges (Test Channel)</li> </ul>	10V, 5V, 1V, 0.1V (selectable)
	<ul> <li>Included I/O</li> </ul>	1 x Ethernet: 10/100Base-T 2 x RS232 (300-115,200 baud) 2 x USB device ports 12 x digital control outputs 12 x digital control inputs 8 x digital status outputs
	<ul> <li>Optional I/O</li> </ul>	1 x USB com port 1 x RS485 Multidrop RS232
Physical Specifications	<ul> <li>Operating Temperature Range</li> </ul>	5 - 40°C
	<ul> <li>Dimensions (H x W x D)</li> </ul>	7" x 17" x 24" (178 x 432 x 609 mm)
	<ul> <li>Weight</li> </ul>	35.5 lbs (16.1 kg) with internal zero air pump

Specifications subject to change without notice.

All specifications are based on constant conditions.

sales@pacwill.ca www.pacwill.ca

